


## I 形鋼 最小曲げ半径

		
H x B x t1	モノレール曲	タテ曲
100 x 75 x 5.0 x 8.0	500	1000
125 x 75 x 5.5 x 9.5	300	1000
150 x 75 x 5.5 x 9.5	1000	2000
150 x 125 x 8.5 x 14.0	1000	2500
180 x 100 x 6.0 x 10.0	1000	2500
200 x 100 x 7.0 x 10.0	1000	5000
200 x 150 x 9.0 x 16.0	1000	5000
250 x 125 x 7.5 x 12.5	1200	6000
250 x 125 x 10.0 x 19.0	1200	6000
300 x 150 x 8.0 x 13.0	1500	7000
300 x 150 x 10.0 x 18.5	1500	7000
300 x 150 x 11.5 x 22.0	1500	7000
350 x 150 x 9.0 x 15.0	1500	8000
350 x 150 x 12.0 x 24.0	1500	8000
400 x 150 x 10.0 x 18.0	1500	10000
400 x 150 x 12.5 x 25.0	1500	10000
450 x 175 x 11.0 x 20.0	1900	12000
600 x 190 x 16.0 x 35.0	1900	15000

**備考**

※ つかみ代についてはお問い合わせ下さい  
 ※ 変形形状は別紙「変形および検査方法」をご覧ください。